



EP-14 ELECTRIC OUTBOARD FEATURES AND BENEFITS

- Reliable and durable construction with minimal maintenance required
- Available in tiller or top- and side-mount throttle control
- All motors available in long- or short shaft models
- Traditional design with standard aluminum casting so replacement parts are readily available
- Water-cooled system that prevents over-heating
- Multiple safety precautions including over-speed protection, overload protection, temperature protection, over-voltage and over-current protection
- Consistent power throughout the speed range
- Brushless PMAC motor that is over 90-percent efficient
- Cruise with peace of mind thanks to our “Get Home Safe” battery alert system
- Motors ranging from 5-HP to 50-HP
- Clean cruising without the hassles and hazards of gasoline
- Low cost of operation when compared to traditional gas motors



TILLER MODEL:



REMOTE MODEL: THROTTLE OPTIONS
Livorsi Side or Top Mount



COMPARABLE GAS/PETROL RATING	14 HP
INPUT POWER (WATTS)	6480 watts
VOLTAGE	48 vdc
MAXIMUM CURRENT	135 amps DC
MOTOR	Brushless PMAC
STATIC THRUST	204 lbs
COOLING SYSTEM	Water cooled
THROTTLE SYSTEM	Remote or tiller option
THROTTLE	Side mount or Top mount option, 16' length
THROTTLE CABLE EXTENSION <small>OPTIONAL</small>	6'
LOWER UNIT GEAR RATIO	2.08:1 (27/13)
GEAR OIL CAPACITY	8.5 oz
TRIM AND/OR TILT	Manual
PROPELLER	3 - 9.25" x 10"
WEIGHT	85 lbs
SHORT SHAFT TRANSOM HEIGHT	17.5"
SHORT SHAFT OVERALL (HEIGHT, WIDTH, LENGTH)	43" x 11" x 18.5"
LONG SHAFT TRANSOM HEIGHT	22.5"
LONG SHAFT OVERALL (HEIGHT, WIDTH, LENGTH)	46" x 11" x 18.5"
MSRP	\$4,110