



EP-20 ELECTRIC OUTBOARD FEATURES AND BENEFITS

- Reliable and durable construction with minimal maintenance required
- Available in tiller or top- and side-mount throttle control
- All motors available in long- or short shaft models
- Traditional design with standard aluminum casting so replacement parts are readily available
- Water-cooled system that prevents over-heating
- Multiple safety precautions including over-speed protection, overload protection, temperature protection, over-voltage and over-current protection
- Consistent power throughout the speed range
- Brushless PMAC motor that is over 90-percent efficient
- Cruise with peace of mind thanks to our “Get Home Safe” battery alert system
- Motors ranging from 5-HP to 50-HP
- Clean cruising without the hassles and hazards of gasoline
- Low cost of operation when compared to traditional gas motors



TILLER MODEL:



REMOTE MODEL: THROTTLE OPTIONS
Livorsi Side or Top Mount



| | |
|---|--|
| COMPARABLE GAS/PETROL RATING | 20 HP |
| INPUT POWER (WATTS) | 8880 watts |
| VOLTAGE | 48 vdc |
| MAXIMUM CURRENT | 185 amps DC |
| MOTOR | Brushless PMAC |
| STATIC THRUST | 240 lbs |
| COOLING SYSTEM | Water cooled |
| THROTTLE SYSTEM | Remote or tiller option |
| THROTTLE | Side mount or Top mount option, 16' length |
| THROTTLE CABLE EXTENSION <small>OPTIONAL</small> | 6' |
| LOWER UNIT GEAR RATIO | 2.08:1 (27/13) |
| GEAR OIL CAPACITY | 8.5 oz |
| TRIM AND/OR TILT | Manual |
| PROPELLER | 3 - 9.25" x 8" |
| WEIGHT | 85 lbs |
| SHORT SHAFT TRANSOM HEIGHT | 17.5" |
| SHORT SHAFT OVERALL (HEIGHT, WIDTH, LENGTH) | 43" x 11" x 18.5" |
| LONG SHAFT TRANSOM HEIGHT | 22.5" |
| LONG SHAFT OVERALL (HEIGHT, WIDTH, LENGTH) | 46" x 11" x 18.5" |
| MSRP | \$4,804 |